



ALUMITEX
SPECIFICATION

ALXV4.30



25MM ALUMINIUM VENETIANS SPECIFICATION

SLAT WIDTH	THICKNESS
25mm	0.18 - 0.21 microns
16mm	0.18 microns

LIST OF COLOURS

COLOUR	SLAT SIZE	HEADRAIL/ BOTTOM BAR	CORD LADDER
9411 (M)	25mm	9411	Mocca
9412 (M)	25mm	9412	Aluminium
Aluminium (M)	16mm & 25mm	Aluminium	Aluminium
Aluminium Filtra (R)	25mm	Aluminium	Aluminium
Anthracite (M)	25mm	Anthracite	Anthracite
Apache (M)	25mm	Apache	Mocca
Aqua (M)	25mm	Aqua	Lilac
Armada (M)	25mm	Armada	Black
Atmosphere (M)	25mm	Atmosphere	Vapour
Atomic (M)	25mm	Energy	Energy
Beige (M)	25mm	Beige	Beige
Beryl (R)	25mm	Majestic	Majestic
Black (M)	16mm & 25mm	Sonar	Black
Black Filtra (R)	25mm	Sonar	Black
Bondi (M)	25mm	Bondi	Navy
Boutique (R)	25mm	Flint	Flint
Brushed Aluminium (R)	25mm	Aluminium	Aluminium
Brushed Linen (R)	25mm	Clarity	Cream
Brushed Sand (R)	25mm	Melodi	Cream
Candyfloss (M)	25mm	Candyfloss	Candyfloss
Canton (R)	25mm	Tahiti	Tahiti
Cerise (M)	25mm	Cerise	Cerise
Citrine (M)	25mm	Citrine	Citrine
Clarity (M)	25mm	Clarity	Melodi
Cool Grey (R)	16mm & 25mm	Umbra	Zircon
Coral (M)	25mm	Coral	Coral
Cream (M)	25mm	Melody	Cream
Cream Filtra (R)	25mm	Pasadena	Cream
Drama (R)	25mm	Primary Red	Primary Red
Dream (M)	25mm	Dream	Dream
Ebon (M)	25mm	Ebon	Soul
Echo (R)	25mm	Clarity	Cream
Electra Blue (R)	25mm	Dream	Atlantis
Electra Gold (R)	25mm	Midas	Electra Gold
Emerald (M)	25mm	Emerald	Emerald
Energy (M)	25mm	Energy	Energy
Estrella Abyss (R)	25mm	Aluminium	Aluminium
Estrella Axis (R)	25mm	Aluminium	Aluminium
Estrella Lyra (M)	25mm	Estrella Lyra	Estrella Lyra
Flame (M)	25mm	Flame	Flame
Flint (M)	25mm	Flint	Shadow Grey
Galleria (R)	25mm	Vapour	Vapour
Glam (R)	25mm	Glam	Latte
Gloss (M)	25mm	Vapour	White



25MM ALUMINIUM VENETIANS SPECIFICATION

COLOUR	SLAT SIZE	HEADRAIL/ BOTTOM BAR	CORD LADDER
Glow (M)	25mm	Glow	Yellow
Graphite (R)	25mm	Onyx	Black
Gravel (M)	16mm & 25mm	Gravel	Aluminium
Grey Filtra (R)	25mm	Shadow Grey	Aluminium
Hunter (M)	25mm	Hunter	Hunter
Ivory (M)	16mm & 25mm	Clarity	Cream
Jazz (M)	25mm	Jazz	Terracotta
Latino (M)	25mm	Latino	Teracotta
Lilac (M)	25mm	Lilac	Lilac
Litra Coca (R)	25mm	Flint	Flint
Litra Fawn (R)	25mm	Melodi	Cream
Litra Putty (R)	25mm	Beige	Lusso
Lusso (R)	25mm	Clarity	Melodi
Luster (R)	25mm	Glam	Latte
Lyra (M)	25mm	Vela	Vela
Majestic (M)	25mm	Puple	Purple
Matt (M)	16mm & 25mm	Vapour	Vapour
Melodi (M)	25mm	Melodi	Melodi
Merle (R)	25mm	Onyx	Black
Mink (M)	25mm	Mink	Mirano
Mintz (M)	25mm	Mintz	Mintz
Mirano (M)	25mm	Mirano	Mirano
Mocca (M)	25mm	Mocca	Mocca
Mono Biscuit (R)	25mm	Clarity	Melodi
Mono Mud (R)	25mm	Flint	Flint
Mono Naco (R)	25mm	Nomad	Shadow Grey
Mono truffle (R)	25mm	Beige	Latte
Navy (M)	25mm	Navy	Navy
Nomad (R)	25mm	Nomad	Shadow Grey
Novella (R)	25mm	Sonar	Black
Ocean (M)	25mm	Ocean	Atlantis
Onyx (M)	25mm	Onyx	Black
Opal (M)	25mm	Opal	Vela
Orion (M)	25mm	Soul	Soul
Pasadena (M)	25mm	Pasadena	Ivory
Pastel Blue (M)	25mm	Pastel Blue	Pastel Blue
Peral (M)	25mm	Pearl	Vapour
Persia (M)	25mm	Persia	Persia
Pistachio (R)	16mm & 25mm	Clarity	Ivory
Porcelain (M)	25mm	Porcelain	Vapour
Powder Green (M)	25mm	Powder Green	Powder Green
Primary Red (M)	25mm	Primary Red	Primary Red
Pulse (M)	25mm	Pulse	Terracotta
Quartz Blue (R)	25mm	Aluminium	Aluminium
Quartz Red (R)	25mm	Aluminium	Aluminium
Rapture Glisten (R)	25mm	Aluminium	Aluminium
Rapture Rebel (R)	25mm	Sonar	Black
Rapture Sonic (R)	25mm	Soul	Soul
Reef (M)	25mm	Reef	Reef



25MM ALUMINIUM VENETIANS SPECIFICATION

COLOUR	SLAT SIZE	HEADRAIL/ BOTTOM BAR	CORD LADDER
Shadow Grey (M)	25mm	Shadow Grey	Shadow Grey
Shelby (M)	25mm	Shelby	Shelby
Sky (M)	25mm	Bondi	Navy
Sonar (M)	25mm	Sonar	Black
Soul (M)	16mm & 25mm	Soul	Soul
Spirit (R)	25mm	Vela	White
Steel Filtra (R)	25mm	Aluminium	Aluminium
Tahiti (M)	25mm	Tahiti	Tahiti
Titanium (R)	16mm & 25mm	Aluminium	Aluminium
Tropic (M)	25mm	Tropic	Tropic
Truth (R)	16mm & 25mm	Vapour	Vapour
Umbra (M)	25mm	Umbra	Zircon
Vanilla (M)	25mm	Melodi	Melodi
Vapour (M)	25mm	Vapour	Vapour
Vela (M)	25mm	Vela	Vela
Vibe Cool Blue (R)	25mm	Pastel blue	Pastel Blue
Vibe Grey (R)	25mm	Atmosphere	Vapour
Vibe Nude (R)	25mm	Vibe Nude	Shadow Grey
Vibe Silver (R)	25mm	Aluminium	Aluminium
Vibe Trance (R)	25mm	Sonar	Black
Vibe Yellow (R)	25mm	Yellow	Yellow
Vitale (R)	16mm & 25mm	Noamd	Aluminium
White Filtra (R)	25mm	Vapour	White
Woodline 9401 (M)	25mm	9401	Electra Gold
Woodline 9403 (M)	25mm	9403	Terracotta
Woodline 9404 (M)	25mm	9404	Mirano
Woodline 9405 (M)	25mm	9405	Latte
Woodline 9406 (M)	25mm	9406	Electra Gold
Woodline 9407 (M)	25mm	9407	Terracotta
Woodline 9408 (M)	25mm	9408	Mocca
Woodline 9409 (M)	25mm	9405	Latte
Woodline 9410 (M)	25mm	9410	White
Yellow (M)	25mm	Yellow	Yellow
Zephyr (R)	25mm	Melodi	Melodi
Zircon (R)	25mm	Soul	Soul
Zora Barley (R)	25mm	Clarity	Cream
Zora Coco (R)	25mm	Vibe Nude	Flint
Zora Haze (R)	25mm	Beige	Beige

COLOUR COORDINATION

- Head rail and bottom bars are colour co-ordinated.
- Blinds manufactured with slats marked 'M' will have colour matching head rail, bottom bar and cords/ladders.
- Blinds manufactured with slats marked 'R' will have the nearest available colour for head rail and bottom rail.
- Standard Tassel: Clear plastic.

MIXED SLAT FINISHES

- Alumitex® is available with a mixed slat finish.
- Surcharge for mixed slats - £8.65
- A waiver must be signed for non-standard requests

DIMENSIONS

SLAT SIZE	HEAD RAIL SIZE	BOTTOM RAIL SIZE
16mm	19mm x 27mm	10mm x 19mm
25mm	24mm x 25mm	11mm x 25mm

SLAT SIZE	MINIMUM WIDTH	MAXIMUM WIDTH
16mm	210mm	1800mm
25mm	210mm	4000mm

*Recommended maximum drop 3050mm

MINIMUM DROP	MAXIMUM DROP
120mm	4000mm

*Recommended maximum drop 3050mm

CONTROLS

RAISE CONTROL	Right hand side (standard)
TILT CONTROL	Left hand side (standard)
TILT OPTIONS	Clear wand

Raise and tilt control can be placed on the opposite side or same side (size restrictions apply)



NUMBER OF LADDERS PER 16MM BLIND

BLIND WIDTH	NO OF LADDERS
Up to 675mm	2
676mm - 1050mm	3
1051mm - 1425mm	4
1426mm - 1800mm	5

Raise and tilt control can be placed on the opposite side or same side (size restrictions apply)

NUMBER OF LADDERS PER 25MM BLIND

BLIND WIDTH	NO OF LADDERS
Up to 850mm	2
851mm - 1400mm	3
1401mm - 1950mm	4
1951mm - 2500mm	5
2501mm +	6

Raise and tilt control can be placed on the opposite side or same side (size restrictions apply)

BRACKETS

- Aluminium venetian blinds come with installation brackets (standard)
- Standard: Top fix/ Face fix
- Optional: End Fix / Extension

STANDARD	Top fix/ Face fix
OPTIONAL	End Fix / Extension

BLIND WIDTH	NO OF LADDERS	END FIX BRACKETS	INSTALLATION BRACKETS
Up to 854	2	2	0
855-1404mm	3	2	1
1405mm-1954mm	4	2	2
1955mm-2504mm	5	2	3
2505mm-3529mm	6	2	4

Raise and tilt control can be placed on the opposite side or same side (size restrictions apply)



Hold down brackets available - £1.00 per blind
Maximum extension is 110mm

STACKING HEIGHT

The stacking height of a blind refers to the measurement from top to bottom when the blind is fully pulled up. These stacking heights should be treated as advice only. There is a slight variance in the slat thickness and in how the slats pack with the ladder therefore each individual blind will be different.

BLIND DROP (MM)	STACKING HEIGHT (MM)
500	55
750	60
1000	70
1250	75
1500	85
1750	90
2000	100
2250	105
2500	110
2750	120
3000	125
3250	135
3500	140



Stack heights are measured from top of headrail to bottom of bottombar when pulled tight. Stack heights are for reference only, variance in slat thickness and how the ladder stacks may alter the actual stack height each time the blind is raised.

CHILD SAFETY

All Alumitex® venetians are child safe compliant. All blinds come with a breakaway safety tassel, cord stop rings and 2-piece cleat. The safety cleat is used to wrap the cord around to keep out of children's reach.

CORD LENGTHS AND INSTALLATION HEIGHTS

- If the installation height is known, the distance from the floor to bottom of pull cords shall be at least 1.5m.
- If the installation height is not known but the drop of the blind is less than 2.5m, the length of the pull cords shall be less than 1m.
- If the installation height is not known but the drop of the blind is more than 2.5m, the length of pull cords shall be less than drop of the blind minus 1.5m.

BLIND TYPE	MINIMUM CONTROL LENGTH (MM)	DEDUCTION MADE WHEN INSTALLATION HEIGHT PROVIDED (MM)	MINIMUM INSTALLATION HEIGHT (MM)
25mm Aluminium	150	1500	2000

For example: For a 25mm Aluminium blind which has an installation height of 3000mm the controls will be 1500mm. Note the wand will be made to the same size as the cords.

Aluminium blinds are produced within a tolerance of +/-3mm width and +/-5mm drop



35/50MM ALUMINIUM VENETIANS SPECIFICATION

SLAT SIZE: 35/50MM
Aluminium (M)
Black (M)
Grey (R)
Magnolia (R)
White (M)
Perforated Aluminium (M)
Perforated Black (M)
Perforated Grey (R)
Perforated Magnolia (R)
Perforated White (R)

- Head rail and bottom bars are colour co-ordinated steel.
- Blinds manufactured with slats marked 'M' will have colour matching head rail, bottom bar and cords/ladders.
- Blinds manufactured with slats marked 'R' will have the nearest available colour for head rail and bottom rail.
- Timberlux valance is available as an additional uplift, please reference 35mm/50mm Alunitex Prime pricing tables.

DIMENSIONS

SLAT SIZE	HEADRAIL SIZE
35mm	38mm x 37mm
50mm	57mm x 51mm

MINIMUM WIDTH	MAXIMUM WIDTH
210mm	3050mm

MINIMUM DROP	MAXIMUM DROP
120mm	3500mm

WOOD VALANCE (OPTIONAL)

SLAT SIZE	WOOD VALANCE
35mm	50mm
50mm	63mm

35/50mm blinds that are sent on Timberlux® headrails are dispatched with Timberlux® box brackets as standard. Timberlux® swivel brackets and extension brackets are available.

TAPES

SLAT SIZE	TAPE
35mm	25mm
50mm	38mm

*Tape options available from the Timberlux® Collection.
Hold down brackets available - £1.00 per blind*

Standard Tassel: Clear Plastic

Optional Tassel: Cylinder 55 brushed aluminium tassel - £6.80 per blind

CONTROLS

	STANDARD	OPTIONAL
RAISE CONTROL	Right hand side	Left hand side
TILT CONTROL	Left hand side	Right hand side
TILT OPTIONS	Cords (All Sizes)	N/A

Blinds with widths 210mm - 300mm have no controls

BRACKETS

- Aluminium venetian blinds come with box brackets with centre supports depending on width. These can be face/ side/ top fixed.
- End fix, Swivel and Extension Swivel brackets are also available.
- Hold down brackets available - £1.00 per blind

STACKING HEIGHT

The stacking height of a blind refers to the measurement from top to bottom when the blind is fully pulled up. These stacking heights should be treated as advice only. There is a slight variance in the slat thickness and in how the slats pack with the ladder therefore each individual blind will be different.

BLIND DROP (MM)	STACK HEIGHT 35MM SLAT (MM)	STACK HEIGHT 50MM SLAT (MM)
500	115	105
750	145	130
1000	170	145
1250	195	170
1500	220	190
1750	245	210
2000	270	230
2250	300	250
2500	325	270
2750	350	290
3000	375	310
3250	400	330
3500	425	350

Stack heights are measured from top of headrail to bottom of bottombar when pulled tight. Stack heights are for reference only, variance in slat thickness and how the ladder stacks may alter the actual stack height each time the blind is raised.

CHILD SAFETY

All Alumitex venetians are child safe compliant. All blinds 35mm/50mm blinds come with a Breakaway Cord Condenser & 2 Piece Safety Cleat

The cord condenser is designed to consolidate the pull cords into one string and to break-away, stopping any loops from forming. The safety cleat is used to wrap the cord around to keep out of children's reach.

CORD LENGTHS AND INSTALLATION HEIGHTS

- If the installation height is known, the distance from the floor to bottom of pull cords shall be at least 1.5m.
- If the installation height is not known but the drop of the blind is less than 2.5m, the length of the pull cords shall be less than 1m
- If the installation height is not known but the drop of the blind is more than 2.5m, the length of pull cords shall be less than drop of the blind minus 1.5m.

BLIND TYPE	MINIMUM CONTROL LENGTH (MM)	DEDUCTION MADE WHEN INSTALLATION HEIGHT PROVIDED (MM)	MINIMUM INSTALLATION HEIGHT (MM)
35/50mm Aluminium	275	1500	2000

For example: For a 35/50mm Aluminium blind which has an installation height of 3000mm the controls will be 1500mm. Note the wand will be made to the same size as the cords.



ALUMINIUM VENETIANS MOTORISATION SPECIFICATION

ALUMITEX® MOTORISATION - 25MM

MOTORISATION OPTIONS
Tilt and Lift 25 with Standard Battery
Tilt and Lift 25 with Mains Power

ADDITIONAL SOMFY OPTIONS
Rechargeable Battery Option*
Dual Battery Wand
12v AC/DC Power Supply
AC Battery Wall Charger
Smooove Wall Switch
Somfy® Solar pack

REMOTE CONTROL OPTIONS
Situo Single Channel Remote
Situo 1 RTS
Situo 1 VAR RTS
Situo 5 VAR RTS
Telis 1 Chronis
Telis 6 Chronis
Telis 16
Somfy® Smooove Wall Switch

***Rechargeable battery option comes with 10 x rechargeable batteries. For optimum control - Situo 5 VAR RTS remote control is recommended.*

ALUMITEX® MOTORISATION - 50MM

MOTORISATION OPTIONS
Somfy Sonesse 40 RTS*
Somfy Sonesse 40 WT*

**RTS - Radio controlled motor
WT - Hard wired motor

REMOTE CONTROL OPTIONS
Situo Single Channel Remote
Situo 1 RTS
Situo 1 VAR RTS
Situo 5 VAR RTS
Telis 1 Chronis
Telis 6 Chronis
Telis 16
Somfy® Smooove Wall Switch

**Somfy® Smooove Wall Switch only available with Somfy Sonesse 40WT.*

***Rechargeable battery option comes with 10 x rechargeable batteries. For optimum control - Situo 5 VAR RTS remote control is recommended.*

BRACKETS FOR MOTORISATION

- All brackets options are available on 25mm Alumitex. End fix brackets are standard on 35/50mm aluminium. Top fix brackets are not available on Sonesse motors.

ALUMITEX